CLAIMS

1. (Currently Amended) A method for determining if an item is a fraudulent item, the method comprising the steps of:

obtaining by radio means a first number from an RFID tag associated with the item or item's packaging:

determining a second number that is a public-key signature <u>visibly</u> printed on the item or item's packaging:

utilizing a public-key cryptographic process and the first number to cryptographically verify the second number; and

determining the product's authenticity based on the verification.

Please cancel claims 2-4

- 5. (Original) The method of claim 1 wherein the step of determining the products authenticity comprises the step of associating the product with an authentic product if the signature is verified, otherwise associating the product with a forged product.
- 6. (Currently Amended) A method of manufacturing a product in order to prevent forgery, the method comprising the steps of:

obtaining by radio means an RFID tag comprising a first number;

determining a second number utilizing the first number and a cryptographic process, wherein cryptographic verification of the second number insures the product's authenticity;

affixing the RFID tag comprising the first number to either the product or the packaging associated with the product; and

affixing the second number to either the product or the packaging associated with the product, so as to be visible.

- 7. (Original) The method of claim 6 wherein the step of obtaining the tag comprising the first number comprises the step of obtaining an RFID tag comprising a unique, or semi-unique unalterable number
- 8. (Original) The method of claim 6 wherein the step of affixing the second number to either the product or the packaging associated with the product comprises the step of printing a cryptographic signature on the product or the product's packaging.

- 9. (Original) The method of claim 6 wherein the step of determining the second number utilizing the first number and a cryptographic process comprises the step of utilizing the first number and a private key to generate the second number.
- 10. (Currently Amended) A method comprising the steps of:

Obtaining by radio means a first number from an RFID tag associated with an item;

obtaining a second number that is a cryptographic signature <u>visibly</u> printed on the item or the item's packaging;

utilizing a public key and the first number to verify the second number; and determining the item's authenticity based on the verification.

11. (Currently Amended) A method comprising the steps of:

obtaining by radio means an RFID tag comprising a first number;

utilizing a private key and the first number to create a second number that is a cryptographic signature, such that cryptographic verification of the second number insures a product's authenticity; and

affixing the second number and the RFID tag to the item or the item's packaging so as to be visible.

Please cancel claims 12-14

15. (Previously Submitted) A product scanner comprising:

an RF tag reader outputting contents of an RFID tag;

an optical scanner outputting a public-key cryptographic signature; and

logic circuitry having the contents of the RFID tag and the public-key cryptographic signature as an input and outputting information as to whether an item is a forgery.

- 16. (Original) The product scanner of claim 15 wherein the logic circuitry utilizes a public key and cryptographic operations to verify the cryptographic signature.
- 17. (Previously Submitted) An apparatus comprising:

an RF reader outputting contents of an RFID tag;

logic circuitry having the contents of the RFID tag as an input and outputting a publickey cryptographic signature based on the contents of the RFID tag; and printing circuitry having the public-key cryptographic signature as an input-and printing, wherein the printing circuitry commands a visible printing of the public-key cryptographic signature upon an item or packaging.

- 18. (Previously Submitted) The apparatus of claim 17 further comprising: an RFID writer outputting product information for the item to the RFID tag.
- 19. (New) The method according to claim 1 wherein a bar code is used for rendering the second number that is printed on the item or item's packaging.
- 20. (New) The apparatus according to claim 1 wherein a bar code is used for rendering the second number that is affixed on the item or item's packaging.